

SAFETY DATA SHEET

Lacquer Cleaner

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION:

DISTRIBUTOR: Griffin Bros., Inc.
P.O. Box 7719
Salem, OR 97303
INFORMATION PHONE: (503) 362-1326
For Medical and Chemical Emergencies CHEMTREC: 1-800-424-9300

USES: Lacquer Thinner is a mixture of solvents able to dissolve a number of different resins or plastics used in modern lacquer.

Use Restrictions: No data available

PRODUCT NAME: Lacquer Cleaner
PRODUCT NUMBER: AA-417
DATE PREPARED: 04/03/2009
LAST REVISION: 06/08/2015

2. HAZARDOUS IDENTIFICATION:

GHS CLASSIFICATION: Flammable liquids (Category 2) Skin irritation (Category 2) Aspiration hazard (Category 1)
Specific target organ toxicity - single exposure (Category 3) Acute aquatic toxicity (Category 1) Chronic aquatic toxicity (Category 4)

GHS Label elements, including precautionary statements:

SIGNAL WORD: **Danger!**

PICTOGRAM(s)



Hazard statement(s)

H225: Highly flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H318: Causes serious eye damage.
H332: Harmful if Inhaled.
H336: May cause drowsiness or dizziness.
H360: May damage fertility or the unborn child.
H400: Very toxic to aquatic life.
H413: May cause long lasting harmful effects to aquatic life.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 Ground/bond container and receiving equipment.
P261 Avoid breathing fume/ mist/ vapours/ spray.
P262 Do not get in eyes, on skin, or on clothing.
P273 Avoid release to the environment.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
P304+P340: IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.

POTENTIAL HEALTH EFFECTS

EYE CONTACT: May cause irritation or damage to the eyes.

INHALATION: Irritating to the nose, throat, and respiratory tract.

INGESTION: Nausea, vomiting, or diarrhea may result from ingestion.

SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SIGNS AND SYMPTOMS OF EXPOSURE: Irritation, pain, coughing, redness of skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS:

Chemical Name	CAS #	Weight Range %
LIGHT ALIPHATIC SOLVENT NAPHTHA	64742-89-8	10 – 20%
2-BUTOXYETHANOL	111-76-2	5 – 15%
ETHYL ACETATE	141-78-6	5 – 15%
METHYL ISOBUTYL KETONE	108-10-1	0 – 10%
METHYL ETHYL KETONE	78-93-3	0 – 10%
ACETONE	67-64-1	0 – 10%
ISOPROPANOL	67-63-0	0 – 10%
ETHANOL	64-17-5	0 – 10%
METHANOL	67-56-1	0 – 10%
TOLUENE	108-88-3	0 – 10%
XYLENES	1330-20-7	0 – 10%
ETHYLBENZENE	100-41-4	0 – 10%

4. FIRST AID MEASURES

- EYE CONTACT:** Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation persists.
- INHALATION:** After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel
- INGESTION:** Induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. Rest. If no medical personnel are available & patient is conscious, ingestion of an alcoholic beverage may prevent blindness, death. Do NOT induce vomiting to an unconscious or convulsing person.
- SKIN CONTACT:** Wash with soap and water. Change contaminated clothing. Get medical attention if irritation develops or persists.

AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin or respiratory conditions.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA:

Dry chemical, foam or carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES:

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece in positive pressure mode. Move containers from fire area if it can be done without risk. Use water to keep fire-exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Extinguish all nearby sources of ignition. Vapors are heavier than air and may travel to distant ignition sources and flash back. Avoid accumulation on water because this product will float on water and possibly ignite.

COMBUSTION PRODUCTS:

Toxic vapors and gasses can be released if involved in a fire.

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Stop spill at source. Dike and contain. Collect leaking liquid in sealable containers. Absorb remaining liquid in sand or inert absorbent. Remove to safe place. Do NOT wash away into sewer. Do NOT let this chemical enter the environment.

7. HANDLING AND STORAGE:

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

HANDLING: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

STORAGE: Keep in fireproof surroundings. Keep separated from strong oxidants, strong acids, food & feedstuffs. Keep cool. Do not store above 49 C/120 F. Keep container tightly closed & upright when not in use to prevent leakage. Do not allow to evaporate to near dryness. Addition of water or proper reducing agents will lessen peroxide formation.

OTHER PRECAUTIONS: Protect from freezing. Follow all SDS/label precautions even after container is emptied because it may retain product residues. For industrial use only. Keep away from children. Keep containers closed while not in use.

8. EXPOSURE CONTROL/PERSONAL PROTECTION:

RESPIRATORY EXPOSURE CONTROLS: A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

Chemical Name	OSHA PEL		ACGIH TLV	
	TWA	STEL	TWA	STEL
XYLENE	100ppm	n/a	100ppm	n/a
TOLUENE	200ppm	n/a	50ppm A4	n/a
METHANOL	200ppm	n/a	200ppm	n/a

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: Wear a NIOSH/MSHA approved respirator appropriate for vapor concentration at point of use.

PROTECTIVE GLOVES: Rubber or other impervious material with gauntlets.

VENTILATION: Local exhaust sufficient to keep exposure below TLV.

WORK / HYGENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before smoking, or using the toilet.

- ENGINEERING CONTROLS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.
- EYE PROTECTION:** Wear safety glasses. If splashing is probable, wear full face shield. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.
- OTHER PROTECTIVE EQUIP:** Boots, apron, lab coat or coveralls of impervious material, safety shower, eyewash.

9. PHYSICAL AND CHEMICAL PROPERTIES:

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

a) Appearance: Clear, colorless liquid	k) Vapor pressure (mm/hg): 69.4
b) Odor: Ketone odor.	l) Vapor density (Air = 1): 2.4
d) pH: No data available	m) Relative density (Specific Gravity):
e) Melting point/freezing point: No data available	n) Water solubility: Moderate
f) Initial boiling point and boiling range: No data available	p) Auto-ignition temperature: 555 °F
g) Flash point: 80 °F Method Used: TCC	r) Viscosity: No data available
h) Evaporation rate: No data available	-) Pounds Per Gallon: 6.736
j) Upper/lower flammability or explosive limits: UEL: n/a LEL: 2.3	VOC'S (>0.44 Lbs/Sq In) : 90.0 Vol. % / 727.9 g/L / 6.063 Lbs/Gal
NONEXEMPT VOC'S (CVOC) : 91.8 Vol. % / 744.1 g/L / 6.198 Lbs/Gal	TOTAL VOC'S (TVOC) : 100.0 Vol. % / 808.8 g/L / 6.736 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS) : 34.4 Wt. % / 278.2 g/L / 2.317 Lbs/Gal	NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C): 51.3
	OTHER: No other data is available for this product. . . .

10. STABILITY AND REACTIVITY:

STABLE: Stable under normal conditions.

INCOMPATIBILITY: The substance can presumably form explosive peroxides under the influence of light and air. Check for peroxide prior to distillation, eliminate if found. Reacts violently with strong oxidants, strong reducing agents, strong acids, causing fire & explosion hazard. Attacks many plastics, rubber, coatings.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Isolate from oxidizers, heat, sparks, electric equipment & open flame.

11. TOXICOLOGICAL INFORMATION:

Routes of Entry: Absorbed through skin. Inhalation.

Chronic Effects on Humans:

May cause damage to the following organs: lungs, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS).

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

12. ECOLOGICAL INFORMATION:

MAMMALIAN INFORMATION:

MATERIAL CAS # LOWEST KNOWN LETHAL DOSE DATA

LOWEST KNOWN LD50 (ORAL)

Ethylene Glycol Butyl Ether 111-76-2 320.0 mg/kg (Rabbits)

LOWEST KNOWN LC50 (VAPORS)

Ethylene Glycol Butyl Ether 111-76-2 700 ppm (Mice)

LOWEST KNOWN LD50 (SKIN)

Ethylene Glycol Butyl Ether 111-76-2 440.0 mg/kg (Rabbits)

AQUATIC ANIMAL INFORMATION:

The most sensitive known aquatic group to any component of this product is:

Goldfish 250 ppm or mg/L (24 hour exposure).

Keep out of sewers and natural water supplies.

The substance is toxic to aquatic organisms.

MOBILITY: This material is a mobile liquid.

DEGRADABILITY: This product is partially biodegradable.

ACCUMULATION: This product does not accumulate or bio-magnify in the environment.

13. DISPOSAL CONSIDERATIONS: Processing, use or contamination may change the waste management options.

Recycle/dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If in doubt, contact appropriate agencies.

14. TRANSPORT INFORMATION:

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
US DOT	1993	Flammable Liquid n.o.s. (Xylene, Toluene, Methanol)	3	II

GUIDE NUMBER: 128

15. REGULATORY INFORMATION:

EPA REGULATION: N/A

SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS CAS# WT % (REG. SECTION) RQ(LBS)

*2-Butoxyethanol 111-76-2 10 (313) None

Ethyl Acetate 141-78-6 10 (311,312) 5000

*Methyl Isobutyl Ketone 108-10-1 8 (311,312,313,RCRA) 5000

Methyl Ethyl Ketone 78-93-3 8 (311,312) 5000

Acetone 67-64-1 8 (311,312) 5000

*Methanol 67-56-1 8 (311,312,313,RCRA) 5000

*Toluene 108-88-3 8 (311,312,313,RCRA) 1000

*Xylenes 1330-20-7 6 (311,312,313,RCRA) 100

*Ethylbenzene 100-41-4 < 2 (311,312,313,RCRA) 1000

> 1667 LB / 758 KG OF THIS PRODUCT IN 1 CONTAINER EXCEEDS THE "RQ" OF XYLENES.

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively.

Failure to report may result in substantial civil and criminal penalties.

State & local regulations may be more restrictive than federal regulations.

16. OTHER INFORMATION:

HMIS INFORMATION: HEALTH: 2 FLAMMABILITY: 3 PHYSICAL HAZARD: 0 PROTECTIVE: X
 NFPA INFORMATION: TOXICITY: 2 FIRE: 3 REACTIVITY: 0

Griffin Bros., Inc. expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Griffin Bros., Inc. makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Griffin Bros., Inc.'s control and therefore users are responsible to verify this data under their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication of use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. Griffin Bros., Inc. expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical source.